

Rudy's

**** Convenience door & fairing cover retainer system ****

DoorKeeper Kit

- **Installs in about 1 minute per side** - No tools required! Both sides included
- **Prevents loss of fairing doors and cubby doors** – Stop losing doors when hinges break
- **Ultra-strong permanent tethers** – Install once and forget it from then on
- Won't rust or make noise
- No holes required – Just clean with isopropyl alcohol and attach.
- 2 Year Materials and Workmanship Warranty! Even the stitching is sealed!

Congratulations on the purchase of your new DoorKeeper kit. This super strong and easy to install kit will save you countless headaches and money by preventing the unexpected loss of your cubby doors and hard fairing pocket doors. It is a one time install and forget system to provide years of trouble free use for your motorcycle.



Installation:

Warning: Successful adhesion is critical. Failure to follow these steps for preparation of the panel to adhere to the special adhesive clip to the panel will likely be cause for failure of the adhesive and possible loss of the part being retained!!! This adhesive is rated at 140 lbs tensile strength and installed temps of -40F to 200F but ONLY if it is installed properly. We will not be responsible for adhesion failure due to improper preparation procedures. Read all directions before starting installation steps.

Note: There are two ABS base clips in the kit with strapping already attached through each of the bases. The offset of the straps is intentional. It allows dynamic optimization of the adhesive strength when the strap is stressed.

1. Open the door to be retained.
2. Clean the inside of the door and the inner-upper part of the inside of the housing where the two bases will be attached with a paper towel and isopropyl alcohol. Let the alcohol dry completely.
3. Be sure to leave room where the edges of the body will meet the door so you don't place the bases where interference will occur. Remember, these base are a one time placement and then they are permanent. If you have to remove one, you will need to obtain another kit for a second chance at it since these are one-shot, permanent bases.
4. Mount a base to the inside of the door first. This way you will be able to decide where best to place the second base by pulling on the mounted base with the strap so that the door rests where you want it to once the base inside the box is placed.

Please contact us about any questions or problems you may have with your DoorKeeper kit installation or operation at support@thefarend.com Any comments or suggestions are always welcome.

We have done our best to make this kit as complete, reliable and easy to install as possible for you.

Thanks for purchasing Rudy's DoorKeeper kit.

Copyright 2010, CME Electronics, Inc and RudysProducts.com